

# D2 - On & Off Road - GAZ892



All Position

## Overview

Rim Size	:	20-24
Aspect Ratio	:	0-95
Section Width	:	11-325
Speed Rating	:	K-K

## Features

- Highway oriented shoulder rib design
- Specially formulated tread compound
- Improved base construction formulation
- Reinforced casing and bead structure
- Incorporation of stone ejector

## Benefits

- Reduces chances of shoulder irregular wear
- Wear resistance for regional / highway roads and mild off road
- Promotes cooler running by insulating tread heat on casing
- Improves durability of casing and bead, increasing tire damage resistance from heavy load operating conditions
- Prevents stone trapping and thereby reduce risk of tire damages

Tire Size	PR	Load Index	Speed Rating	Approved Rim	Outer Diameter (mm)	Tread Depth (mm)	Max Load (kg)	Max Pressure	
								kPa	PSI
10.00R20	16	146/143	K	7.5	1052	15.3	3000/2725	830/830	120/120
11.00R20	16	150/147	K	8	1085	15.3	3350 / 3075	830 / 830	120 / 120
12.00R20	18	154/151	K	8.5	1125	15.3	3750 / 3450	830 / 830	120 / 120
325/95R24	22	162/160	K	9.00	1228	17	4750/4500	850/850	123/123